

The world's best way to make coffee



 **THE MIDDLEBY CORPORATION**

La Cimbali has been a front-runner in the development of espresso and cappuccino culture for decades. The group operates in more than 100 countries and distributes its products exclusively through Celfrost in India. It has even launched a special single group traditional coffee machine "Celfrost Professional" for the Indian market.

Cimbali products are patronized by Barista Lavazza, Coffee Beans & Tea Leaf Company and many more names in the hotel & hospitality industry.

Cimbali machines are extraordinarily reliable and all over the world you will find baristas who will testify to the long life of their Cimbali. The Cimbali product range includes traditional and superautomatic espresso coffee machines, coffee beans grinders and accessories.

Superautomatic Machines

Q 10 MilkPS 11



Recommended cups per day: up to 100

- MilkPS
- Smart Boiler
- Wi-Fi connectivity (optional)
- Compact size
- Variable Coffee Group Chamber

Dimensions (mm)			Weight (kg)	Voltage (50-60Hz)	Power (W)	Phase
W	D	H				
350	630	670	48.5	220-240V~	2000-2300	Single

S 20



Recommended cups per day: up to 200

- MilkPS
- 7.0" touch screen, up to 24 drink selections
- HQ Milk
- Metal coffee group
- Smart Boiler
- AWS - Automatic washing system
- Wi-Fi connectivity
- USB Port
- Bi-directional Telemetry

Dimensions (mm)			Weight (kg)	Voltage (50-60Hz)	Power (W)	Phase
W	D	H				
370	620	762	71	220-240V~	3200-3800	Single



Traditional Machines

M34 SELECTRON



- 2, 3 groups
- TurboSteam Milk4 (optional)
- PGS
- Smart Boiler
- Mixed Water
- Thermo Drive
- Green Machine
- USB Port
- Bluetooth

	Boiler Capacity (litres)	Dimensions (mm)			Weight (kg)	Voltage (50-60Hz)	Power (W)	Phase
		W	D	H				
2 groups	10	770	510	510	70	380-415V3N~	4200-4900	Three
3 groups	15	970	510	510	85	380-415V3N~	6200-7300	Three



M39 DOSATRON



- 2, 3, 4 groups
- Electronic programming of coffee and hot water dosage
- Smart Boiler technology (patented)
- Turbosteam (patented) optional in place of the right standard steam wand
- 2 standard steam wands
- 1 hot water wand
- 2 hot water selections
- Graphic display
- Electric cup warmer (3 temperature settings)
- Silver style body

Also available in the tall cup version

	Boiler Capacity (litres)	Dimensions (mm)			Weight (kg)	Voltage (50-60Hz)	Power (W)	Phase
		W	D	H				
2 groups	10	855	570	565	105	380-415V3N~	4500-5500	Three
3 groups	15	1055	570	565	129	380-415V3N~	6700-8400	Three
4 groups	20	1255	570	565	154	380-415V3N~	6700-8400	Three





LA CIBALI

Traditional Machines

M21 JUNIOR



- 1 group
- Electronic programming of coffee dosage
- 1 standard steam wand
- 1 hot water wand
- Silver style body
- Also available in the semiautomatic version

Dimensions (mm)			Weight (kg)	Voltage (50-60Hz)	Power (W)	Phase
W	D	H				
430	612	793	65	220-240V~	3100-3600	Single



M23 UP



- 2 groups
- Electronic programming of coffee dosage
- 2 standard steam wands
- 1 hot water wand
- Stainless steel and black metal body
- Automatic version

Boiler Capacity (litres)	Dimensions (mm)			Weight (kg)	Voltage (50-60Hz)	Power (W)	Phase
	W	D	H				
11	820	518	552	63	220-240V~	4800	Three



M100 DT2



- 2 groups
- 2 steam wands
- 1 Turbo Steam
- Milk4
- Cold Touch wand
- 1 steam wand tall cup version
- Hot water & steam (10 ltr)

Boiler Capacity (litres)	Dimensions (mm)			Weight (kg)	Voltage (50-60Hz)	Power (W)	Phase
	W	D	H				
11	820	518	552	63	220-240V~	4800	Three



UNDICI A1



- 1 group
- Electronic programming of coffee dosage
- 1 standard steam wand
- 1 hot water wand
- Elegant red & stainless steel body
- Thermal balancing system
- Built in volumetric pump
- Pump & boiler preserve double gangs
- Automatic boiler fill

Boiler Capacity (litres)	Dimensions (mm)			Weight (kg)	Voltage (50-60Hz)	Power (W)	Phase
	W	D	H				
4.9	432	598	670	33	220-240V~	3000-3500	Single



UNDICI A2



- 2 groups
- Electronic programming of coffee dosage
- 1 standard steam wand
- 1 hot water wand
- Elegant red & stainless steel body
- Thermal balancing system
- Built in volumetric pump
- Pump & boiler preserve double gangs
- Automatic boiler fill

Boiler Capacity (litres)	Dimensions (mm)			Weight (kg)	Voltage (50-60Hz)	Power (W)	Phase
	W	D	H				
10.5	712	598	570	57	380-415V3N~	4000-4400	Three



Coffee Dosing Grinders

MAGNUM ON DEMAND Instantaneous, electronic grinder-doser

- 64 mm flat grinding burrs
- Output: 13 kg / h
- Hopper capacity: 1.6 kg



Dimensions (mm)			Voltage (50-60Hz)	Power (W)	Phase
W	D	H			
220	400	620	220V~	300	Single



MAGNUM Automatic grinder

- 75 mm flat grinding burrs
- Output: 11 kg / h
- Hopper capacity: 1.6 kg



Dimensions (mm)			Voltage (50-60Hz)	Power (W)	Phase
W	D	H			
220	400	620	220-240V~	350	Single
220	400	620	380-415V3N~	350	Three



JUNIOR Manual grinder



- 64 mm flat grinding burrs
- Output: 7.5 kg / h
- Hopper capacity: 0.75 kg

Dimensions (mm)			Voltage (50-60Hz)	Power (W)	Phase
W	D	H			
220	360	430	220-240V~	300	Single



Multifunctional Commercial Blender



Rio® - HBB250 CE

- 25 second Daiquiri
- 450 Watts
- 1/2 HP with pulse
- 1.25 L Polycarbonate Jar
- Rubber clutch
- Wave-Action® System
- Dimensions (WxDxH): 165 x 203 x 406 mm



Tempest® - HBH650 CE

- 12 second Daiquiri
- 1,000 Watts
- 3 HP with pulse
- 1.9 L Polycarbonate Jar
- Metal clutch
- Time/auto shutoff
- Jump cycle
- Jar pad sensor
- Wave-Action® System
- Dimensions (WxDxH): 178 x 203 x 457 mm



Summit® - HBH850 CE

- 12 second Daiquiri
- 1,000 Watts
- 3 HP with pulse
- 1.9 L Polycarbonate Jar
- Auto blend
- Quiet Shield
- Time/auto shutoff
- Cavitation control
- Cycle blending
- Jar pad sensor
- Converts to under-counter
- Metal clutch
- Wave-Action® System
- Dimensions (WxDxH): 229 x 305 x 478 mm



CB-606D
(Programmable Control)

- 6 Programme Control with Pulse
- Rated/Peak Power 1650W/2500 W
- Max Speed 28000 rpm
- Jar Capacity : 2 Ltr
- Heavy Duty, Copper Motor, SS coupling
- Over heat & Over load protection
- CE, CB Certified
- Dimensions (WxDxH): 200 x 240 x 495 mm



CB-606
(Speed Control)

- Speed Control with Pulse
- Rated/Peak Power 1650W/2500 W
- Max Speed 28000 rpm
- Jar Capacity : 2 Ltr
- Heavy Duty, Copper Motor, SS coupling
- Over heat & Over load protection
- CE, CB Certified
- Dimensions (WxDxH): 200 x 240 x 495 mm

- Speed Control, Timer and Pulse with Acoustic Enclosure
- Rated/Peak Power 1650W/2500 W
- Max Speed 28000 rpm
- Jar Capacity : 2 Ltr
- Heavy Duty, Copper Motor, SS coupling
- Over heat & Over load protection
- CE, CB Certified
- Dimensions (WxDxH): 260 x 360 x 510 mm



CB-699



0.9 Ltr. JAR
Suitable for CB 606 / 606D / 699



Middleby Celfrost Innovations (P) Ltd.

Corp. Office : Unit Nos. SF-713 — 716, 7th Floor, JMD Megapolis, Sohna Road, Sector 48, Gurgaon - 122 018, Haryana, India.
Tel. : +91 124 482 8500, Fax : +91 124 427 9663, E-mail : corp@middlebycelfrost.com, Web : www.middlebycelfrost.com

Toll Free Customer Service No.: 1800-102-1980 • service.india@middlebycelfrost.com

ONE PARTNER. ONE TEAM. MANY SOLUTIONS.



For sales related queries :-

Call: +91 124 4828500 • Email: sales@middlebycelfrost.com